



FPGWORLD.COM

# INLINE

## 3000 SERIES BAIN MARIE 800 ON-COUNTER/CURVED HEATED

|              |                               |
|--------------|-------------------------------|
| RANGE        | INLINE 3000 SERIES BAIN MARIE |
| TEMPERATURE  | HEATED                        |
| MODEL        | IN-3B08-CU-FF-OC              |
| FRONT        | CURVED/FIXED FRONT            |
| INSTALLATION | ON-COUNTER                    |
| HEIGHT       | 770mm                         |
| WIDTH        | 803mm                         |
| DEPTH        | 663mm                         |

|                                      |                |
|--------------------------------------|----------------|
| TEMPERATURE RANGE                    | +30°C - +110°C |
| RECOMMENDED CORE PRODUCT TEMPERATURE | +65°C - +80°C  |
| ENVIRONMENTAL TEST CONDITIONS        | 22°C / 65% RH  |

### FEATURES

- High energy efficiency: 0.73 kWh per hour (average)
- Cabinet operating temperature range +30°C - +110°C  
Recommended core product temperature +65°C - +80°C

- Smart display with toughened safety glass encased in brushed stainless steel frame

#### Fixed Front Heated Display

- Fitted with halogen heat lamps, with 3000 hour warm white lighting
- Supplied with 2x 1/1 gastronorm dishes 65mm deep
- Extrusions at the top and bottom of the cabinet - front only - are fitted with stainless steel panels that can be replaced with branded inserts

#### Operational Excellence

- Sliding doors (staff side) and fixed front (customer side)
- Constructed from stainless and mild steel with toughened safety glass and double-glazed end panels for maximum energy efficiency, climate control and durability
- Low-wattage, high-density element provides even temperature distribution
- Dry operation well only
- Positioned on counter top



Showing :Inline 3000 Series Bain Marie heated 800mm curved on-counter fixed front

### OPTIONS & ACCESSORIES

Contact a [FPG Sales Representative](#) for our full range, including:

- Add a holding shelf
- Branded decals/inserts
- Rear door or end glass mirror application
- GN pans (various sizes)
- GN dividers
- Forward-facing controls
- Custom joinery solution



Indicates sustainability benefits



Please contact FPG to discuss your requirements for meeting country-specific standards.

FPGWORLD.COM



FPGWORLD.COM

# INLINE

## 3000 SERIES BAIN MARIE 800 ON-COUNTER/CURVED HEATED

### HEATED DATA

| MODEL            | TEMPERATURE RANGE | RECOMMENDED CORE PRODUCT TEMPERATURE | ENVIRONMENTAL TEST CONDITIONS | HEATING  |
|------------------|-------------------|--------------------------------------|-------------------------------|--|
| IN-3B08-CU-FF-OC | +30°C – +110°C    | +65°C – +80°C                        | 22°C / 65% RH                 | Low-wattage, high-density element / 2x 100 watt linear halogen |

### ELECTRICAL DATA

| MODEL            | VOLTAGE   | PHASE  | CURRENT | E24H (kWh) | kWh per hour (average) | IP RATING | MAINS                 |                              | HEAT LAMPS                 | HALOGEN LIGHTING |            |
|------------------|-----------|--------|---------|------------|------------------------|-----------|-----------------------|------------------------------|----------------------------|------------------|------------|
|                  |           |        |         |            |                        |           | CONNECTION            | CONNECTION PLUG <sup>1</sup> |                            | HOURS            | COLOUR     |
| IN-3B08-CU-FF-OC | 220-240 V | Single | 4.8 A   | 17.52      | 0.73                   | IP 22     | 3 metre, 3 core cable | 10 amp, 3 pin plug           | 2x 100 watt linear halogen | 3000             | Warm white |

<sup>1</sup>Please advise country to change plug specification.


### CAPACITY, ACCESS & CONSTRUCTION

| MODEL            | DISPLAY AREA       | NO. OF 1/1 PANS | ACCESS FRONT | ACCESS REAR   | CHASSIS CONSTRUCTION         |
|------------------|--------------------|-----------------|--------------|---------------|------------------------------|
| IN-3B08-CU-FF-OC | 0.3 m <sup>2</sup> | 2               | Fixed front  | Sliding doors | Stainless 304 and mild steel |


### DIMENSIONS

| MODEL            | H x W x D mm (Uncrated) | MASS (Uncrated) |
|------------------|-------------------------|-----------------|
| IN-3B08-CU-FF-OC | 770 x 803 x 663         | 62 kg           |


Crated weights and dimensions vary. Please contact us for information on your shipment.




PLAN VIEW



FRONT ELEVATION



SECTION VIEW



REAR ELEVATION

More information including technical data and installation guidelines is available from the Product Manual published on our website.

In line with our policy to continually develop, improve and support our products, Future Products Group Ltd reserves the right to change specifications and design without notice.

Have a question? Please email us at [sales@fpgworld.com](mailto:sales@fpgworld.com) or visit [www.fpgworld.com](http://www.fpgworld.com) for full contact details for your region.



Worldwide contact details: